

Hard Knocks.

Our unyielding H07BQ-F
industry cable always
stands its ground.



The planet's pathways



Our unyielding H07BQ-F industry cable always stands its ground.

Our termination and connection cable H07BQ-F is ready to get to terms with the toughest environments. Being highly resistant to everything from temperatures and mechanical stress to abrasion, this cable is ready to power up all sorts of heavy-duty appliances. Add to that protection against moist, chemicals and grease – this cable is worth every pound.



Wide range of applications

Perfect choice for tooling and engineering, cold storages or freezers – or even as an extension cable.



Full flexibility

The polyurethane material is making the cable highly pliable.



Impact resistant

Able to withstand intense force over a short period of time.



Bare copper conductor

Rubber insulation

Polyurethane sheath



Hardwearing

Robust PUR sheathing makes H07BQ-F resistant to high mechanical stress.



UV resistant

Designed to be used both indoors and out, in rain, snow and sunshine.



Liquid proof


Resistant to chemicals, grease as well as water.

Click or scan QR-code for → complete product information



PRYSMIAN

Prysmian MKM Kft.
Phone: +36 1 382 2222
infocables-hu@prysmiangroup.com



prysmiangroup.hu

© All rights reserved by Prysmian 2024-01 | Version 2.

Technical data, dimensions and weights are subject to change. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian.

Follow us

